

Appliance Efficiency Standards Workshop California Energy Commission

SDG&E/SoCalGas Appliance Efficiency Efforts

Presented by Jerine Ahmed and Jon McHugh

January 15, 2008

Introduction

- Advocate improvements to appliance efficiency standards
- Undertake Codes and Standards Enhancement (CASE)
 Studies in support of CEC's Appliance Efficiency
 Standards
- Collaborative effort with IOU's to harmonize activities and avoid duplication of efforts
- Coordinate efforts with stakeholders including CEC, industry, trade associations, manufacturers



Current & Future Efforts

- Focused on appliances without Federal Standards, not at risk of federal preemption
- Develop test standards
- Establish minimum performance standards
- Current and Future Efforts:
 - Commercial Gas Dryer presented in detail
 - Commercial Radiant Heaters
 - Gas Convection Oven
 - Burner Flame Control
 - Barbeques and Patio Heaters
 - Air Curtains
 - Collaboration with other IOUs



Commercial Gas Dryer Standards

Presented by:

Heschong Mahone Group
On behalf of SDG&E and
SoCalGas

January 15, 2008



Introduction

- DOE definition for clothes dryer:
 - A cabinet-like appliance designed to dry fabric in a tumble-type drum with forced air circulation
- Use gas or electricity as heating source
- Commercial gas dryers are similar to residential clothes dryer, but for different applications:
 - Coin laundries: Laundromat and multi-family housing
 - On-premise laundries: hospitality industry, retirement facilities, hospitals, restaurants, health clubs, salons and spas, correctional facilities, fire departments, schools



Efficiency Standards Status

- Federal regulations cover residential clothes washers and dryers, and commercial washers
- DOE is trying to update standards for residential clothes dryer (last meeting held in October 2007)
- DOE has no plan on developing standards for commercial gas dryers





Market Overview

- About 2 3 million of commercial washer/dryer installed in the United States, with 10% replaced every year
- About 70% of the commercial application use gas

New commercial gas dryer installation in California: ~16,000/year

 Commercial gas dryers are used much more frequently than residential gas dryers!



Commercial Gas Dryer Technology

Typical 7.5Kg Tumble Dryer

A tumble dryer require at least 25litres of drum volume for each 1kg of washing to be dried, eg 185 litres for this 7.5Kg machine.



Moisture control programmer.

Through drum heating from back to front, through damp washing.

Energy consumption determined by:

- Component efficiency (combustion system and motor)
 - Control scheme
 - Simple timer control
 - Sensing temperature in the exhaust
 - Sensing moisture in the drum
 - "perma-press" cycle: use cold air at the end of the cycle
- Gas modulation
- Flow pattern control inside the drum



Energy Savings Potential

- DOE savings estimation for potential standards improvement for residential gas dryers:
 - ~ 0.06 quads (cumulative from 2008 to 2030)
- Commercial laundry energy consumption represents about 14% of total domestic laundry
- Typically commercial dryer operated > 416 cycles/year
- Average gas consumption: ~0.17 Therms/cycle
- California savings potential: ~ 0.3 Million therms/year



Proposed New Commercial Dryer Appliance Standard

- Adopt testing standards and require manufacturers to list certified performance data
 - Based on federal residential clothes dryer test standards
 - Improvements for distinguishing performance of advanced controls from simple timer control
- Establish tier 1 minimum performance standards, which are equivalent to federal residential gas dryer standards
 - Energy factor: 2.67 lbs/kWh
- Require the use of high-efficiency motors
- Require moisture sensor control

